

Universe	Professional
Type	Verticality
Category	Harnesses
Subcategory	Fall arrest and work positioning harness



VOLT® WIND European Version


The VOLT WIND fall-arrest and work positioning harness is very quick to don, thanks to the FAST LT PLUS and FAST LT buckles that allow it to be donned with both feet on the ground. The wide, semi-rigid waistbelt and leg loops provide excellent support. Its lightweight, breathable construction maximizes air flow. Its LADDER CLIMB attachment point allows for ventral attachment of the fall-arrest trolley, providing optimal comfort during progression. It has wear protectors on the waistbelt and dorsal point to limit wear when moving about inside the wind turbine tower. It is certified to European and Russian standards.



The harness has dorsal wear protectors, to reduce wear on the straps when moving about inside a wind turbine tower.



The waistbelt and leg loops are equipped with FAST LT PLUS and FAST LT buckles, allowing the harness to be easily donned while keeping both feet on the ground. These buckles retain their adjustment settings between donnings.



For vertical progression with a rail or cable-based fall protection system, the LADDER CLIMB attachment point allows for ventral attachment of the trolley, which distributes the load on the waistbelt and provides optimal comfort. In the event of a fall, this attachment point automatically moves upward to a sternal position, allowing a vertical post-fall body position.



The wide, semi-rigid waistbelt and leg loops provide excellent support. Its lightweight, breathable construction maximizes air flow.

Short Description

Fall-arrest and work positioning harness for the wind power industry with attachment point for vertical progression on rail or cable-based fall protection system

Selling Points

- It has wear protectors on the waistbelt and dorsal point to prevent strap wear and provide optimal comfort when moving about inside the wind turbine tower
- Quick and easy donning:
 - Waistbelt equipped with a FAST LT PLUS buckle for quick and easy fastening and unfastening without loss of adjustment, even while wearing gloves
 - FAST LT leg loop buckles allow the harness to be easily donned with both feet on the ground and retain their adjustment settings between donnings
 - DOUBLEBACK self-locking buckles on waistbelt and shoulder straps for precise adjustment
 - Leg loop foam position can be adjusted for ideal positioning
- Comfortable throughout the workday:
 - Wide, semi-rigid waistbelt and leg loops for excellent support and lightweight, breathable construction to maximize air flow
 - Padded shoulder straps are widely spaced to reduce neck chafing and help distribute the load over the shoulders when the waistbelt is loaded
 - LADDER CLIMB ventral attachment point adapts to a variety of uses (progression, positioning, and occasional suspension), and allows the user to connect a lanyard, descender, or fall-arrest trolley; for vertical progression with a rail or cable-based fall protection system, the LADDER CLIMB attachment point allows for ventral attachment of the trolley, which distributes the load on the waistbelt and provides optimal comfort, in the event of a fall, this attachment point automatically moves upward to a sternal position, allowing a vertical post-fall body position
- Easy to use:
 - Side attachment points can be folded down to prevent accidental snagging when not in use
 - Stowing system for the MGO connectors on fall-arrest lanyards are located on each shoulder strap; in the event of a fall, the system releases the MGO connectors and allows the absorber to be deployed
 - Equipment loops, as well as slots for CARITool tool holder and TOOLBAG tool pouch make it easy to organize work tools

Specification

- LADDER CLIMB ventral attachment point: Connection of a positioning lanyard in single mode use, a descender, or a fall-arrest trolley
 - Side attachment points: For attaching a positioning lanyard for use in double mode
 - Sternal attachment point: For attaching a fall-arrest system
 - Dorsal attachment point: For attaching a fall-arrest system
 - Rear waistbelt attachment point: For attaching a restraint lanyard
 - Certification(s): CE EN 361, CE EN 358, CE EN 813, UKCA, EAC, JSFAD
 - Material(s): Nylon, polyester, aluminum, steel
-

Specifications by reference

Reference(s)	C072BA00	C072BA01	C072BA02
Color(s)	Black/Yellow	Black/Yellow	Black/Yellow
Size	0	1	2
Waist belt	65-80 cm	70-93 cm	83-120 cm
Leg loops	44-59 cm	47-62 cm	50-65 cm
Stature	160-180 cm	165-185 cm	175-200 cm
Weight	2150 g	2200 g	2280 g
Made in	RO	RO	RO
Guarantee	3 years	3 years	3 years
Inner Pack Count	1	1	1
Quantity Per Box	3	3	3
EAN	3342540831049	3342540831056	3342540831063

Spare part(s) Lanyard connector holder