

| Universe | Professional | |
|-------------|---------------------------|--|
| Туре | Verticality | |
| Category | Connectors | |
| Subcategory | Semi-permanent connectors | |



RING OPEN

The RING OPEN gated ring is designed for semi-permanent connection of equipment. The round shape allows it to function optimally in all directions. It has a large opening that allows installation of ropes with sewn terminations.



Wide opening allows installation of ropes with sewn terminations.

| Short Description | Multidirectional gated ring | | |
|-------------------|---|--|--|
| Selling Points | Ring designed for semi-permanent connection of equipment Round shape for optimal functioning in all directions Wide opening allows installation of ropes with sewn terminations Available in yellow or dark gray | | |
| Specification | Major axis strength: 23kN Minor axis strength: 23kN Opening: 11 mm Weight: 70g Certification(s): CE EN 362, UKCA Material(s): Aluminum, plastic | | |

Specifications by reference

| Reference(s) | P28 | M028AA00 |
|------------------|---------------|---------------|
| | | |
| Color(s) | Yellow | Dark gray |
| Made in | FR | FR |
| Guarantee | 3 years | 3 years |
| Inner Pack Count | 1 | 1 |
| Quantity Per Box | 25 | 25 |
| EAN | 3342540098589 | 3342540839786 |

Related product(s)

PROGRESS PROGRESS ADJUST ABSORBICA-Y